

AC Submersible Pump Datasheet

Model	HP	Head (Mtr)	Discharge (LPM)	Outlet Size (Inch)	PV Array Min. Watts	Motor Voltage (V)	Speed (RPM)
KE0112	1	30	32	1.25"	335*3	3Ø 72V	2850*
*KE0116	1	50	24	1.25"	335*3	3Ø 72V	2850
KE0112	1	30	50	1.25"	335*3 or 550*2	3Ø 72V or 60V	2850
KE0115	1	50	25	1.25"	335*3 or 550*2	3Ø 72V or 60V	2850
KE0208	2	30	140	2"	335*6 or 550*4	3Ø 160V or 120V	2850
KE0212	2	50	75	1.5"	335*6 or 550*4	3Ø 160V or 120V	2850
KE0218	2	70	60	1.25"	335*6 or 550*4	3Ø 160V or 120V	2850
KE0220	2	80	50	1.25"	335*6 or 550*4	3Ø 160V or 120V	2850
KE0225	2	100	30	1.25"	335*6 or 550*4	3Ø 160V or 120V	2850
KE0308	3	30	200	2"	335*9 or 550*6	3Ø 230V or 160V	2850
KE0310	3	40	150	2"	335*9 or 550*6	3Ø 230V or 160V	2850
KE0312	3	50	130	2"	335*9 or 550*6	3Ø 230V or 160V	2850
KE0315	3	60	120	2"	335*9 or 550*6	3Ø 230V or 160V	2850
KE0318	3	70	95	1.5"	335*9 or 550*6	3Ø 230V or 160V	2850
KE0320	3	80	90	1.5"	335*9 or 550*6	3Ø 230V or 160V	2850
KE0325	3	100	55	1.25"	335*9 or 550*6	3Ø 230V or 160V	2850
KE0504	5	30	480	3"	335*15 or 550*9	3Ø 380V or 260V	2850
KE0506	5	50	280	2.5"	335*15 or 550*9	3Ø 380V or 260V	2850
KE0518	5	70	150	2"	335*15 or 550*9	3Ø 380V or 260V	2850
KE0520	5	80	140	2"	335*15 or 550*9	3Ø 380V or 260V	2850
KE0525	5	100	120	2"	335*15 or 550*9	3Ø 380V or 260V	2850